CHAPTER VII

IDF RESEARCH EXPERIMENTS

In this chapter is described the protocol for conducting research experiments in the following areas:

1. IDF ANALYSIS AND BALANCING OF LIFE FUNCTIONS ASSOCIATED WITH STATES OF WELL BEING

   - ☯ Systems and Organs Programs (Positive Life Functions)
   - ☯ Pathogens Program (Negative Interference Influences)
   - ☯ Affirmation Program (Psychological)
   - ☯ 40 Tuning Program (Metaphysical/Cellular)
   - ☯ Agricultural Program (Environmental and Food Clearing)

2. IDF POTENTIZING, REPLICATING AND ENERGIZING

   - ☯ Potentizing Program
   - ☯ Energetic Replication and Transfer Procedures

3. IDF CUSTOM PROGRAMS

   - ☯ Personal Programs for Balancing
   - ☯ Personal Programs for Analysis

4. IDF COMPATIBILITY ANALYSIS AND BALANCING

   - ☯ Personal Relations, Products, Substances and Places Evaluation Procedures
   - ☯ Testing and Predictive Benefits Assessment of Food, Substances, Products and Environmental Factors
   - ☯ Clear and Neutralize IDF Reactions to Items Tested

IDF RESEARCH PROGRAMS

PROGRAM OPERATIONS. The major categories of IDF research are each represented by permanent memory programs contained in the computer. These includes:

SYSTEMS AND ORGANS PROGRAM (Reference Pages VII 10-13)

PATHOGENS PROGRAM (Reference Pages VII 13-14)

SUBTLE BALANCE PROGRAM (Reference Pages VII 20)

AFFIRMATION PROGRAM (Reference Pages VII 21)

AGRICULTURAL PROGRAM (Reference Pages VII 22)

POTENTIZING PROGRAM PROCEDURE (Reference pages VII 23-25)

CUSTOM PROGRAMS AND COMPATIBILITY ANALYSIS PROCEDURES
(Reference Pages VII 26-28)

DOWNLOADING PROGRAMS FROM THE SE-5 1000 PC SOFTWARE INTO THE
SE-5 1000. (Reference pages VII 34-35)

The contents and procedures for each of the above programs are described in the following pages.

RESEARCH PROTOCOL FOR ALL PROGRAMS

CLEARANCES

1. Ground for static electricity: touch grounded metal object then Amplitude knob.

2. Turn instrument On/Off button to ON.

3. Wait for Cell to clear. (The display will read "Clear Cell, Please Wait". When it is finished clearing the Cell, the display will go the Main Menu.

4. Insert the sample in the cell on the back side of instrument. For more about a good Sample read page VI 12.

5. Turn instrument buttons to MEASURE, NORMAL, 100, ON, Amplitude at 000. Use the arrows ↓↑ and scroll until you get to the Biofield program. Press ENTER. Then press Enter again when it says CLEARANCES. ADDRMVNOWAM appears on the screen. Measure from 100 until stick is felt. If the reading is below 90, switch to Balance with Amplitude knob at 100 for about 30 seconds. Repeat the same procedure from 000. If reading is above 10, switch to Balance with amplitude at 000 for about 30 seconds or until reading is below 10. (To enter the Balance mode, press the Measure/Balance button until it says BAL in the digital display.)

6. Push ↓ and 100-0 ENERGY PURITY appears on the screen. Amplitude must be 85 or over, otherwise it is not appropriate to continue ... stop. If 85 Amplitude or over, continue. See Rub Plate instructions on page VI 7-8.

7. Push ↓ 13-78 INTERFERENCE A appears on the screen. Measure from 000 Amplitude. If Amplitude Readout is over 10 ... stop. Change rooms or angle of instrument, take another measure. If over 10 Amplitude, do not continue. See Problem Solving Page VI 12.

8. Push ↓ 29-80 INTERFERENCE B appears on the screen. Repeat Step 7 procedure.

9. Push ↓ 50-57 INTERFERENCE C appears on the screen. Repeat Step 7 procedure.

10. Push ↓ 70-79 INTERFERENCE D appears on the screen. Repeat Step 7 procedure.

11. Push ↓ 53-28 INTERFERING FIELD appears on the screen. Measure Amplitude from 000. If above 10 Amplitude, set Amplitude at 000 and turn Measure/Balance switch to BALANCE. After 20 seconds return BALANCE to the MEASURE position, take measurement from 000. Should be less than 10 Amplitude or repeat balance procedure for longer period of time until Amplitude measure is below 10.

12. Push ↓ 39-59 BARRIERS TO RAPPORT appears on the screen. Repeat instructions for Step 11.

13. Push ↓ 9-49 VITALITY appears on the screen. Switch on MEASURE. Measure Amplitude from 100 and record on **Chart 1 BIOFIELD RESEARCH MANUAL** page VII 10 in space provided.

    SPECIAL NOTE: Read discussion on Amplitude dial and readout, pages VI 7-10.

14. Push ↓ 43-28 ALKALINE/ACID appears on the screen. Switch on MEASURE. Measure Amplitude from 100. If less than 85, set Amplitude to 100 and Measure/Balance switch to BALANCE. After 20 seconds switch Measure/Balance switch to MEASURE and measure again. Repeat until Amplitude is above 85. Set Measure/Balance switch on MEASURE.

15. Push ↓ 37-93 SODIUM CHLORIDE appears on the screen. Measure from 100. Repeat instructions for Step 14.
    NOTE: To conduct prebalancing programs go to Step 16. To continue analysis push ↓, go to Step 20.

16. Press [Close], to exit program and conduct general balancing sequence Step 17.

PROGRAM OPERATIONS:

17. SUBTLE BALANCE PROGRAM. Set Measure/Balance switch to BALANCE, set 100/1000 switch to 100, Amplitude at 50. Press [Close] until you get to the Main Menu. Press ↓ down arrow until you get to Main Programs then press [Enter]. Press ↓ down arrow again until you get to Subtle Balance Program and press [Enter].
    Auto or Manual: Press [Enter] when it says AUTO on the display.
    Balancing Time: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want each Tuning to Balance then press [Enter].
    Delay: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want to wait between before the next Tuning is Balanced.
    Number of Cycles: Press ↓ down arrow or ↑ up arrow to adjust the amount of times you want the program to repeat itself before it completes.

    Set the SE-5 *1000* into the Balance mode (by pressing the Measure / Balance button until you see BAL in the display in the lower left hand corner) and then press [ENTER].

    After the SE-5 *1000* finishes the Balancing, go to Step 18 (once a program is complete it will return to the Main Menu.)

18. AFFIRMATION PROGRAM. Set Measure/Balance switch to BALANCE, 100/1000 switch to 100 and Amplitude readout at 100. Press ↓ down arrow until you get to Main Programs then press [Enter]. Press ↓ down arrow again until you get to the Affirmations Program and press [Enter].
    Auto or Manual: Press [Enter] when it says AUTO on the display.
    Balancing Time: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want each Tuning to Balance then press [Enter].
    Delay: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want to wait between before the next Tuning is Balanced.

Number of Cycles: Press ↓ down arrow or ↑ up arrow to adjust the amount of times you want the program to repeat itself before it completes.

Set the SE-5 *1000* into the Balance mode (by pressing the Measure / Balance button until you see BAL in the display in the lower left hand corner) and then press [ENTER].

After the SE-5 *1000* finishes the Balancing, go to Step 19 (once a program is complete it will return to the Main Menu.) Details on page VII 21.

19. AGRICULTURAL PROGRAM. Set Measure/Balance switch to BALANCE, 100/1000 switch to 100, Amplitude Readout to 50 and Press ↓ down arrow until you get to Main Programs then press [Enter]. Press ↓ down arrow again until you get to the Agricultural Program and press [Enter].
Auto or Manual: Press [Enter] when it says AUTO on the display.
Balancing Time: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want each Tuning to Balance then press [Enter].
Delay: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want to wait between before the next Tuning is Balanced.
Number of Cycles: Press ↓ down arrow or ↑ up arrow to adjust the amount of times you want the program to repeat itself before it completes.

Set the SE-5 *1000* into the Balance mode (by pressing the Measure / Balance button until you see BAL in the display in the lower left hand corner) and then press [ENTER].

After the SE-5 *1000* finishes the Balancing, go to Step 20 (once a program is complete it will return to the Main Menu.) Details on VII 22.

20. POSITVE PROGRAM. (**Chart 1**, Pages VII 10-13) Set Measure/Balance switch to MEASURE and 100/1000 switch to 100. Amplitude at 100. Press ↓ down arrow until you get to the Biofield Program then press [Enter]. Press ↓ down arrow again until you get to Systems and press [Enter]. Press ↓ down arrow again until you get to Intake Clearances and press [Enter]. (If you have already completed the Intake Clearances, press ↓ down arrow until you get to Biofield and then press [Enter].
Auto or Manual: Press [Enter] when it says MANUAL on the display.

All headings under Sections 1-19 are Positive and are indicated by a + before the description. For all + Tunings measure from 100 Amplitude and record reading in the PRE (prior to balancing) column to the right of the page. All + readings should not be less than 90. Press ↓ to go to the next Tuning.

21. NONPOSITIVE PROGRAM. (**Chart 1**. Pages VII 13-14) Set Measure/Balance Switch to MEASURE, Normal/Scan to NORMAL, 100/1000 Switch to 100. Press Press ↓ down arrow until you get to Biofield Programs then press [Enter]. Press ↓ down arrow again until you get to Pathogen IDFs and press [Enter]. Press ↓ down arrow again until you get to the Pain IDFs Program and press [Enter].
Auto or Manual: Press [Enter] when it says MANUAL on the display.

All entries are negative and measured from 000 Amplitude. All measures over 10 are recorded in the PRE column to the right. Press ↓ to go to the next Tuning.

22. After completion of the analysis on **Chart 1** prioritize the worst readings (eg. highest negatives or lowest positives) recorded in the PRE column on **Chart 1** and record them in the appropriate ranking on **Chart 2**, Page VII 15. **Chart 2** is basically a worksheet for organizing **Chart 1**.

23. From **Chart 1**, or if used **Chart 2**, starting with Sections 20- 26 (Negatives) then Sections 1-19 (Positives), Balance one at a time the Sections that need to be Balanced. For example if you had several Tunings from Section 4, Nutrition Metabolic System, that needed to be Balanced, run that section in Auto mode and Balance those Tunings just like we did with the Subtle Balance Program, Agricultural Program, etc.

TO BALANCE

24. Set Measure/Balance switch to BALANCE, 100/*1000* switch to 100, Amplitude Readout to 0 and Press ↓ down arrow until you get to Biofield Programs then press [Enter]. Press ↓ down arrow again until you get to the Negative IDFs and press [Enter].
Press ↓ down arrow again until you get to the Section you need to Balance (from Chart 2) and press [Enter].

Auto or Manual: Press [Enter] when it says AUTO on the display.
Balancing Time: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want each Tuning to Balance then press [Enter].
Delay: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want to wait between before the next Tuning is Balanced.
Number of Cycles: Press ↓ down arrow or ↑ up arrow to adjust the amount of times you want the program to repeat itself before it completes.

Set the SE-5 *1000* into the Balance mode (by pressing the Measure / Balance button until you see BAL in the display in the lower left hand corner) and then press [ENTER].

After the SE-5 *1000* finishes the Balancing, go to Step 25 (once a program is complete it will return to the Main Menu.)

25. Continue Balancing each Negative Section that needs to be Balanced from Chart 2.

26. Set Measure/Balance switch to BALANCE, 100/*1000* switch to 100, Amplitude Readout to 100.0 and Press ↓ down arrow until you get to Biofield Programs then press [Enter]. Press ↓ down arrow again until you get to the Positive IDFs and press [Enter].
Press ↓ down arrow again until you get to the Section you need to Balance (from Chart 2) and press [Enter].

Auto or Manual: Press [Enter] when it says AUTO on the display.
Balancing Time: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want each Tuning to Balance then press [Enter].
Delay: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want to wait between before the next Tuning is Balanced.
Number of Cycles: Press ↓ down arrow or ↑ up arrow to adjust the amount of times you want the program to repeat itself before it completes.

Set the SE-5 *1000* into the Balance mode (by pressing the Measure / Balance button until you see BAL in the display in the lower left hand corner) and then press [ENTER].

After the SE-5 *1000* finishes the Balancing a program, it will return to the Main Menu.

OPTIONS

Option 1:
To conduct the quickest scan of an issue or problem connect to your PC and in the first window of the New Session Wizard, next to PRIMARY CAUSE OF type in "your problem" and scan **the Main Sections** to identify the subject area for the problem. Scan each subheading of the **BIOFIELD RESEARCH MANUAL (in your software)** and scan each section until the specific problem is located. Once a yes (stick) response is obtained press [Select] and see if the Amplitude measure indicates a worsening of the problem. If so, enter that Tuning into the program by pressing [Enter] and when finished with all sections Balance the program.

Option 2:

Chart 4 of the **BIOFIELD RESEARCH MANUAL** is used to scan for other research modalities which may help the problem(s). Page VII 18.

Type into the computer "OPTIMAL MODALITY FOR PROBLEMS." (Click on the W icon in your toolbar in your SE-5 1000software) Set Normal/Scan switch to SCAN, Measure/Balance switch at MEASURE, 100/*1000*/*10000* switch to 100, and Amplitude at 100.

Insert locator probe and scan **Chart 4** Research Methods List for response. Type into computer response and take Amplitude measure for highest amplitude strengths and prioritize. Refer subject to other approaches or get the contents of these research categories in the INTERMEDIATE COURSE TEXT & DVD offered through your dealer.

PROCEDURAL TIPS FOR USING THE **BIOFIELD RESEARCH MANUAL** RESEARCH PART 1 SECTIONS 1-29

- ☯ All underlined words in the text are for organizational purposes only, do not use for analysis or balancing.

- ☯ Sections and subsections are organized by energy flow and are not always in any alphabetical order.

- ☯ Use of " " marks in left hand Tuning columns relate to the actual use of the word as a Tuning. When indicated type the description into the computer.

- ☯ Use of XX or 100 indicates a place to substitute another Tuning, i.e., XX-100 may be combined with 40-XX to equal 40- 100, etc. See Section 29, left hand and right Tunings for summary listing.

- ☯ The Rx symbol indicates the IDF surrounding prescription drugs. Also type in mg. if indicated or desired.

- ☯ Any product, substance or reagent may be placed on the input plate and/or typed into the computer to analyze for any compatibility responses with any Tunings or word descriptions.

- ☯ All Tunings or words preceded by a + should have Amplitude above Vitality.

- ☯ All Tunings or words **not** preceded by a "+" should read below 10 Amplitude and are to be analyzed from and balanced at an Amplitude of 000.

It is recommended that all negative subtle energies be first neutralized at zero before balancing positive energies. Most positive IDF imbalances, excesses and deficiencies are due to the presence of interfering or negative subtle energies. Most positive energies will return to a more normal amplitude strength once negative energies are removed, If this is not the case, check the structure and function subsections of the **BIOFIELD RESEARCH MANUAL** for each problem area.

(Note: Section titles 1-19 preceded by a " +" do not have a numerical Tuning or code. The word descriptions are the actual IDF reference.)

Important Note:

If the SE-5 goes through a x-ray at the airport, (always ask to have it hand checked then sometimes you won't need this procedure) and before using the SE-5 a) turn on the SE-5 and run the X-Ray Program.

Set Measure/Balance switch to BALANCE, 100/*1000* switch to 100 and Amplitude readout at 100. Press ↓ down arrow until you get to Main Programs then press [Enter]. Press ↓ down arrow again until you get to the X-Ray Program and press [Enter].
Auto or Manual: Press [Enter] when it says AUTO on the display.

Balancing Time: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want each Tuning to Balance then press [Enter]. (10 seconds is good)
Delay: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want to wait between before the next Tuning is Balanced. (1 second is good)
Number of Cycles: Press ↓ down arrow or ↑ up arrow to adjust the amount of times you want the program to repeat itself before it completes. (6 cycles should be enough)
The screen will show "REMOVE X-RAY RADIATION FROM SE-5", and will balance for about one minute.

Set the SE-5 *1000* into the Balance mode (by pressing the Measure / Balance button until you see BAL in the display in the lower left hand corner) and then press [ENTER].

After the SE-5 *1000* finishes the Balancing it will return to the Main Menu and you can continue your Session.

.

CHART 1

IDF SYSTEMS RESEARCH ANALYSIS CHART

NAME: _____ DATE: _____

(SESSIONS)

INTAKE CLEARANCES		PRE	1	2	3	4	5
ADDDRMVNOWAM	Protection @ 100 and @ 000						
+100-0	Energy Purity @ 85+						
13-78	Interferences A @ 000						
29-80	Interferences B @ 000						
50-57	Interferences C @ 000						
70-79	Interferences D @ 000						
53-28	Interfering Fields @ 000						
39-59	Barriers to Rapport @ 000						
+9-49	General Vitality _____						
+43-28	Balance Alkaline Acid						
+37-93	Balance Sodium Chloride						
☯	SECTION 1 SYSTEM AND ORGANS						
+	BIOFIELD SYSTEM						
+100-00-100	Polarities						
+91-41	Subtle Bodies Innate Intelligence						
+906 2775	Energy Centers - Chakras						
+77.9-82	Directional						
+89-98	Meridians						
+29-35	Elements						
☯	SECTION 2						
+	PSYCHOLOGY SYSTEM						
+620-745	Primary						
+1501505	Positive Emotions						
☯	SECTION 3						
+	CELLULAR SYSTEM						
+979-989	Cell						
+4822	Cells of the Body						
+885-968	Cytoplasm						
+964-972	Nucleus						
+82.4-89.5	Cell Salts						
+11-100	Reserve Vitality						
☯	SECTION 4						
+	NUTRITION/METABOLIC SYSTEM						
+43-28/37-93	Metabolic Balance						
+6789	Gases						
+84.6-93.5	Acids						

Chart 1 continued

		PRE	1	2	3	4	5
+4095	Sugars						
+44-33/4515	Proteins/Amino Acids						
+30339	Vitamins						
+64-24.5	Minerals						
+885-469	Supplements						
☯	SECTION 5+ NEUROLOGICAL SYSTEM						
+11-82	Brain						
+37-26	Frontal Lobes						
+99-79	Cortex						
+9975	Forebrain						
+3333	Midbrain						
+3432	Hindbrain						
+00-15	Pons						
+28-13	Medulla Oblongata						
+58-82	Meninges						
+5297	Cerebral Spinal Fluid						
+5-62	Nerves						
+2208	Cranial Nerves						
+39.5-27.5	Vagus Nerve						
+40.5-22	Spinal Cord						
+3367	Nerve Plexus						
+31.75-27.75	Peripheral Nerves						
☯	SECTION 6						
+	ENDOCRINE SYSTEM						
+259	Hormones						
+68-97	Pineal						
+40.5-34.5	Thalamus						
+18-42	Hypothalamus						
+06-87	Pituitary						
+74-65	Anterior						
+56-23	Posterior						
+06-81	Thyroid						
+86-04	Parathyroid						
+59-77	Thymus						
+09-70	Pancreas						
+03-09	Adrenals						
☯	SECTION 7						
+	HEMATOLOGIC SYSTEM						
+9.5-48.5	Blood						
+36-17	Lymph						
+04-95	Spleen						

Chart 1 continued

☯ SECTION 8

+	IMMUNE SYSTEM
+13-29	Non-Allergenic
+59.7-67.4	Non-Specific-Blood
+72.1-84.89	Cell Mediated-Bone
+98.5-72.66	Antibodies, Antigen-Hormonal (Also see Section 27)

☯ SECTION 9

+	OPHTHALMOLOGICAL SYSTEM
+35-18	Eyes
+03.8-02.8	Vision

☯ SECTION 10

+	OTORHINOLARYNGOLOGIC SYSTEM
+94-24	Ears
+6766	Hearing
+51-53	Nose
+29-33	Sinuses
+76-37	Throat
+16-77	Esophagus
+24-07	Pharynx
+75-16	Tonsils
+32-16	Larynx
+31.8-75.4	Trachea

☯ SECTION 11

+	ORAL/DENTAL SYSTEM
+11-81	Mouth
+34-60	Tongue
+39-24	Parotids
+04-99	Teeth
+03-25	Gums
+43-42	Jaw

☯ SECTION 12

+	PULMONARY SYSTEM
+92-83	Lungs
+63-74	Bronchi

☯ SECTION 13

+	CARDIOVASCULAR SYSTEM
+20-70	Heart
+02-98	Aorta
+16-14	Valves
+82-71	Blood Vessels

PRE	1	2	3	4	5

Chart 1 continued

PRE 1 2 3 4 5

☯ SECTION 14

+ GASTROINTESTINAL SYSTEM

+31.3-22	Omentum
+77-84	Stomach
+16-25	Duodenum
+00-82	Small Intestine
+90-66	Cecum
+21-69	Ileocecal Valve
+03-08	Appendix
+22-90	Colon
+50-12	Rectum

☯ SECTION 15

+ HEPATIC/BILIARY SYSTEM

+17-29	Liver
+13-64	Gall Bladder

☯ SECTION 16

+ RENAL/UROLOGIC SYSTEM

+03-82	Kidneys
+00-67	Ureters
+39-30	Bladder
+00-86	Urethra

☯ SECTION 17

+ REPRODUCTIVE SYSTEM

+10-61	Uterus
+27.4-37.4	Cervix
+92-31	Vagina
+59-92	Breasts
+62-54	Ovaries
+05-91	Prostate
+06-88	Penis
+5.9-11	Testes/Gonads
+04.5-100	Sexuality

☯ SECTION 18

+ MUSCLE/SKELETAL SYSTEM

+11-41	Muscles
+61-21	Connective Tissue
+79-52	Joints
+25-22	Bones
+46-27	Spine

Chart 1 continued

☯ SECTION 19

+	DERMATOLOGIC SYSTEM	PRE	1	2	3	4	5
+59-25	Skin						
+08.5-48	Facial						
+08-62	Hair						
+60.5-72.5	Nails						

☯ SECTION 20 PATHOGENS PROGRAM

20-90	PAIN SYNDROMES SYSTEM						
14.5-27	Everywhere						
79.5-XX	Location						
31-XX	Location						

☯ SECTION 21 (Sections 22-26 Possible Sources of Infection)

67-52	INFECTIONS						
55-100	Inflammations						
40-100	Congestion						
15-100	Septic Infection						
35-100	Pus						
23-100	Ulcers						
50-81	Abscesses						
61-100	Cysts						
13-100	Tumors						
63-61	Chlamydial						
69-68	Rickettsial						
54-100	Necrotic Tissue						

☯ SECTION 22

45-79.5	BACTERIA						
60-60	Gram Negative (Typhoid)						
65.5-40.5	Gram Positive (Staph & Strep)						
59-57	Aerobic (Fevers)						
54-59	Mycobacteria (Tuberculosis)						
50-70	Spirochette (Syphilis)						
54-60	Anaerobic Toxins (Tetanus,..)						

☯ SECTION 23

01-65	VIRAL						
36-66	Arbovirus and Arenavirus						
22-44	Central Nervous System						
50-66	Enteroviral						
45-56	Exanthematous						
26-50	Respiratory						
82-68	Systemic						

Chart 1 continued

☯ SECTION 24

63-40 FUNGUS AND PARASITES

		PRE	1	2	3	4	5
80-79	Fungus Systemic						
05.5-100	Molds						
19-100	Parasites						
59-19.5	Worms						
59-32	Protozoal						
10.9-48.5	Nematodes						
35-45.5	Trematodes						

☯ SECTION 25

70-62 ENVIRONMENTAL AGENTS

38-41	Electromagnetic						
69-40	Radiation						
706 2704	Physical Injury						

☯ SECTION 26

70-68 TOXINS/POISONS/PESTS

44-100	Toxins						
901	Poison, Toxins						
38.75-28.75	Drug Poisons						
48.75-48.75	Metal Poisons						
49.25-49.25	Chemical Poisons						
26-26	Pests						
47-13	Food Poisoning						
18-36	Plants, Insecticides						
98-20	Detoxification						
158 5455	Overstimulate						

CHART 2
IDF RESEARCH SUMMARY CHART

Name _____ Date_____

Vitality _____

NEGATIVE IDF IMBALANCES (Sections 20-26) PRIORITY ORDER (Highest First)

1.
2.
3.
4.
5.
6.
7.
8.
9.
10.

POSITIVE IDF LOCATIONS (Sections 1-19) AMPLITUDES LESS THAN 90%

1.
2.
3.
4.
5.
6.
7.
8.
9.
10.

COMBINATION OF NEGATIVE IDF IMBALANCES (Section 20-26_ WITH POSITIVE IDF LOCATIONS (Sections 1-19), PRIORITY ORDER

1.
2.
3.
4.
5.
6.
7.
8.
9.
10.
11.
12.
13.
14.
15.
16.
17.
18.
19.
20.

CHART 3
IDF RESEARCH LOCATION ANALYSIS CHART

For Each Problem Location Scan For Cause

NEGATIVE ENERGIES	Section
POLARITIES	1
CHAKRAS	1
MERIDIANS	1
ELEMENTS	1
PSYCHOLOGICAL	2
Negative	2
Positive	2
CELLULAR	3
Nuclear Wall/ DNA	3
NUTRITION	4
Protein	4
Minerals	4
Vitamins	4
BRAIN CENTERS	5
Motor Areas	5
Sensory Areas	5
Association Areas	5
NERVES	5
Cranial	5
Spinal Cord	5
Peripheral	5
HORMONES/SECRETIONS	6
Pineal	6
Thalamus	6
Pituitary	6
Thyroid	6
Parathyroid	6
Thymus	6
Pancreas	6
Adrenals	6
Ovaries	17
Gonads	17
Stomach	6
Small Intestines	6
Kidneys	6
Gall Bladder	15
Liver	15
CIRCULATION	7
BLOOD	7
LYMPH	7
IMMUNE	7
MUSCLES	19
CONNECTIVE TISSUE	19
BONES	19
JOINTS	19
DISCS	19
VERTEBRAE	19
NEGATIVE ENERGIES	2
PAIN	20
INFECTION	21
BACTERIA	22
VIRAL	23
FUNGUS	24
MOLDS	24
PARASITES	24
ELECTROMAGNETIC	25
RADIATION	25
INJURY	25
POISONS/TOXINS	26
Chemical	26
Metal	26
Drug	26
Pesticide / Insecticide	26
Inhaled	26
Ingested	26
Absorbed	26
ALLERGIES	8&27

SPIRITUAL BODY.....31.5-16.5
CAUSAL BODY.....17.5-58
MENTAL BODY.....48-27
EMOTIONAL BODY.....25-47
ETHERIC BODY.....49-57
CONSCIOUS MIND.....80-74
SUBCONSCIOUS MIND.....48-55
INNATE INTELLIGENCE.....91-41

CHART 4

IDF RESEARCH METHODS ANALYSIS CHART

RESEARCH METHOD	SECTION (PART II)
AURA, METAPHYSICAL AND PARAPSYCHOLOGICAL: IDF RESEARCH	SECTION 1
ACUPUNCTURE: IDF RESEARCH	SECTION 2
ALLOPATHIC: IDF RESEARCH	SECTION 3
CHIROPRACTIC: IDF RESEARCH	SECTION 4
DENTISTRY: IDF RESEARCH	SECTION 5
HOMEOPATHIC: IDF RESEARCH	SECTION 6
NATUROPATHIC: IDF RESEARCH	SECTION 7
COLOR AND SOUND	A
ELECTRICAL AND ELECTROMAGNETIC	B
FLOWERS AND AROMATICS	C
GEMSTONES AND CRYSTALS	D
GEOMETRICS	E
HERBS	F
MASSAGE	G
REMEDIES	H
NUTRITION: IDF RESEARCH	SECTION 8
OSTEOPATHIC: IDF RESEARCH	SECTION 9
PODIATRY: IDF RESEARCH	SECTION 10
PSYCHOLOGICAL: IDF RESEARCH	SECTION 11

NOTE: The detailed contents of this chart are not included with this manual. **Chart 4** represents the Table of Contents for the Intermediate Training Manual. The Intermediate Training Manual with accompanying DVD is available as the Intermediate Training Course and may be purchased from your dealer.

NOTES

CHART 5

Name _____ Date _____

SUBTLE BALANCE PROGRAM - Description contains both high and low amplitude as indicated by + or -. FOR BALANCING: Switch on Balance, Normal, *1000*, On.
FOR ANALYSIS: Switch on Measure, Normal, *1000*, On. Press ↓to move to next entry.

+ Align Chakras -	906 2775	_____	____
+ Aural Balance -	942 4459	_____	____
- Auto-Toxicity -	697 5766	_____	____
+ Balance -	297 0309	_____	____
- Blockages -	628 3100	_____	____
+ Calc Fluor -	335 6653	_____	____
+ Calc Phos -	485 7759	_____	____
+ Calc Sulph -	675 6755	_____	____
+ Ferr Phos -	835 4451	_____	____
+ Kali Mur -	295 3555	_____	____
+ Kali Phos -	365 1558	_____	____
+ Kali Sulph -	365 5057	_____	____
+ Mag Phos -	525 2752	_____	____
+ Nat Mur -	255 3154	_____	____
+ Nat Phos -	735 5158	_____	____
+ Nat Sulph -	225 3752	_____	____
+ Silicea -	585 5855		
+ Brow Chakra -	106 0351	_____	____
+ Crown Chakra -	365 6055	_____	____
+ Heart Chakra -	666 0094	_____	____
+ Navel Chakra -	166 7509	_____	____
+ Root Chakra -	562 6565	_____	____
+ Spleen Chakra -	226 6565	_____	____
+ Throat Chakra -	283 7859	_____	____
- Congestion -	401 0060	_____	____
+ Coordination -	893 0409	_____	____
+ Subtle Body Coord. -	308 9805	_____	____
- Deficiencies -	584 5601	_____	____
- Poisons-Toxins -	706 8755	_____	____
+ Environment -	668 5858	_____	____
- Fluorine -	612 6570	_____	____
- Miasms -	753 2153	_____	____
+ Let Miasm Energy Flow -	751 5055	_____	____
+ Use Miasm Energy Beneficially -	323 7525	_____	____
- Oral Anomalies -	952 5605	_____	____
- Overstimulation -	158 5455	_____	____
- Physical Injury -	706 2704	_____	____
+ Rays -	853 5655	_____	____
- Vaccines -	751 5259	_____	____
+ Vitality -	949 0000	_____	____

CHART 6

Name _____ Date _____

IDF AFFIRMATIONS - All descriptions should be high amplitude.
FOR BALANCING: Switch on Balance, Normal, *1000*, On.
FOR ANALYSIS: Switch on Measure, Normal, *1000*, On Press ↓to move to next entry.

I am free of negative blockages and influences.	_____	_____I
am free of negative control lines.	_____	_____I
am protected from negative influences.	_____	_____
I am full of white light.	_____	_____
I am in harmony with the universe.	_____	_____
I am totally healthy and getting younger.	_____	_____
Mother and I are one.	_____	_____
I control my life and forgive everyone.	_____	_____
I release all negative thoughts and feelings.	_____	_____
I release all negative emotions.	_____	_____
I release all hates and fears.	_____	_____
I release all angers and frustrations.	_____	_____
I am humble and grateful for my many talents.	_____	_____
I radiate love.	_____	_____
My goals are high and I reach them easily.	_____	_____
I work inspired.	_____	_____
I am open to new beliefs.	_____	_____
I seek to improve.	_____	_____
I have complete self-assurance.	_____	_____
I can relax fully at any time I desire.	_____	_____
I am decisive.	_____	_____
I do things now without putting them off.	_____	_____
I am rewarded with wealth and success.	_____	_____

CHART 7

Name _____ Date _____

AGRICULTURAL ALIGNMENT TUNING PROGRAM - Descriptions contain both high and low Amplitudes as indicated by a + or -.
FOR BALANCING: Switch on Balance, Normal, *1000*, On. Beeps at end of cycles and repeats.
FOR ANALYSIS: Switch on Measure, Normal, *1000*, On. Press ↓to move to next entry.

+ Acid-Alkaline -	853 5155	_____
+ Align Energy -	906 2554	_____
- Ammonia -	517 6931	_____
- Animals	796 2539	_____
+ Balance -	297 0587	_____
- Blockages -	628 3178	_____
+ Calcium -	886 1682	_____
- Chemical Poisons -	707 5739	_____
+ Coordination -	893 0409	_____
+ Copper -	626 1791	_____
- Deficiencies -	584 5234	_____
+ Environment -	668 5859	_____
+ Helium -	239 1430	_____
- Insects -	321 4401	_____
+ Iron -	910 1967	_____
+ Magnesium -	547 1559	_____
+ Manganese -	053 1518	_____
+ Nitrogen -	806 1760	_____
- Overstimulate -	158 5182	_____
+ Phosphorus -	946 1317	_____
+ Porosity -	253 1255	_____
+ Potassium -	089 1249	_____
+ Rays -	853 5443	_____
- Self-Pollution -	697 5404	_____
- Silicon -	048 1408	_____
- Soil Overwork -	779 8641	_____
+ Soil Vibrations -	887 4561	_____
- Sulfur -	487 1555	_____
- Toxins -	172 6774	_____
+ Vitality -	949 0000	_____
+ Vortex A -	106 0555	_____
+ Vortex B -	365 6666	_____
+ Vortex C -	666 0777	_____
+ Vortex D -	166 7444	_____
+ Vortex E -	562 6888	_____
+ Vortex F -	226 6333	_____
+ Vortex G -	283 7111	_____
+ Vortex Coord. -	308 9671	_____
- Water Pollution -	569 9872	_____
+ Zinc -	969 1598	_____

POTENTIZING PROGRAM

EXPERIMENTS TO POTENTIZE AND ENERGIZE SUBSTANCES
(Measure and balance as appropriate per instructions)

PURPOSE:

To determine the optimal energy levels required by a subject and to energize substances to that identified energy level. Potentization program is used in instances where balancing broadcasts are not feasible or when there are long term or permanent imbalances requiring maintenance or where a potentized substance provides additional support to a balancing session or in between sessions.

This is not a homeopathic procedure, but a potentizing process. Only persons licensed to practice homeopathy are allowed to treat with homeopathic remedies.

POTENTIZE --

OPERATING PROCEDURES

First - clear substance/product to be potentized

1. Set Measure/Balance switch to BALANCE, 100/*1000* switch to 100 and Amplitude readout at 100. Press ↓ down arrow until you get to Main Programs then press [Enter]. Press ↓ down arrow again until you get to the Remove Negative Energy Program and press [Enter].
   Auto or Manual: Press [Enter] when it says MANUAL on the display.
   The screen will show "REMOVE NEGATIVE ENERGY".

2. Place sample to be potentized on rub plate (see Note at end).

3. Set Amplitude Readout to 100. Switch on Balance, Normal, *1000*, On. Wait 20 seconds.

4. Remove substance/product from Rub Plate and place onto Input Plate. Set Measure/Balance switch to MEASURE, 100/*1000* to 100.

5. Take an Amplitude measurement from 100. If above 85 continue, if not repeat Step 3 for a longer period and repeat Steps 4 & 5 to be certain the Amplitude readout is above 85.

Option #1 Operate the Potentizing Program for Replicating

1. Place the orginal substance that you would like to replicate on the LEFT hand spiral coil on the top of your SE-5 *1000*.

2. Place the substance/product that you cleared earlier on the RIGHT hand spiral coil on the top of your SE-5 *1000*.
3. Press the seven pointed STAR button to the right of your Amplitude knob.

4. When the light stops blinking, the process is complete.

Option #2 Operate the Potentizing Program from your PC program

1. Turn on your computer and then start the SE-5 1000program.
2. Connect your USB cable to your computer and to the SE-5 *1000*.
3. On the top menu bar, Click on Balancing then on Potentize.

On the computer screen will appear TYPE IN NAME AND POTENCY THEN PRESS START.

4. Type into the computer the name of the substance/product and/or the Tuning you want to be potentized. Make sure the product/substance to be potentized is on the Input Plate. Set the Amplitude readout to 000 and while turning the Amplitude knob ask yourself, "What potency level is needed?" When you get a stick on the plate look at the Amplitude and record the number on the **Chart 9**, page VII 25.

5. Type in the potency number from Step #4 and type an X directly after the potency number, eg., 9-49 Immune Pak 10X (a Tuning, a product description and the potency)

6. Type in the number of second required to potentize the substance.

9. Place the product/substance from the Input Plate onto the Rub Plate and set the SE-5 *1000* into the Balance mode (by pressing the Measure / Balance button until you see BAL in the display in the lower left hand corner). Set the Amplitude to 100 and press the [ENTER] key. A progress bar appears on the computer screen.

10. After the product/substance is potentized press the [Close] button to close the potentizing window. Remove the product/substance from the plate. (If the product/substance is for another research subject do not handle it but put it in a protective container.)

As with any potentized-type material, keep the potentized preparations in a dark bottle and in a cool place to help preserve the energy content. Heat, light, magnetic fields, vibration, shock and interfering radiations seem to degrade any potentized material. Note that you are able to check your operating technique (and stored preparations) by measuring the potency using the SE-5.

NOTE: Always potentize substances in pure glass containers like pyrex, not plastic. The energies can be mixed and you end up with potentized formaldehyde.

CHART 9
POTENTIZING PROGRAM

Name _____ Date _____

POTENCY PROGRAM – Click on Balancing/then Potentizing in your SE-5 1000program. Type in Tuning and potency then press [ENTER].

Use X potency for less than 100 Amplitude.
Use C potency for above 100 Amplitude, scale switch to *1000* Use M potency for above *1000* Amplitude, scale switch to 10,000.
All readings are approximate.

SUBSTANCE	DESCRIPTION/TUNING	POTENCY	BASE
1.			
2.			
3.			
4.			
5.			
6.			
7.			
8.			
9.			
10.			

Note: This chart is not intended for preparation of homeopathic remedies. Its purpose is for experimental research studies designed to examine whether such potency correlations exist in Intrinsic Data Fields.

CUSTOM PROGRAM

EXPERIMENTS IN CUSTOM PROGRAM SEQUENCING
(Measure and balance at Amplitude zero for negative, 100 for positive, 50 for both negative and positive)

PURPOSE:

To enter into memory a sequenced custom or individualized program containing Tunings of the operator's choice.

PROCEDURE: (Example, any content desired)

Operator entered Tunings from:

1. Results of analysis from programs in permanent memory.
2. A compilation of information from research Tuning books.
3. Personal messages of desired goals, objectives or needs, e.g. anything you want.

FEATURES:

Custom programs can be stored up to about 200 programs depending on their length. For example, if you write Custom programs with about 40 Tunings each, you would be able to make about 150 programs. If you make your programs with *1000* Tunings each, you could only make about 5 Custom programs.

☯ Custom programs will stay in memory (won't erase when running other programs).

☯ Custom programs have separate, selectable time intervals for automatic recall.

OPERATING PROCEDURES:

After making your Sessions in your PC with your SE-5 1000 sofware, click on the Session Manager.
Check off the Sessions you would like to export.
Then click on [SEND TO SE-5] and the programs will be transferred to your SE-5 *1000*.

After successfully downloading the programs into your SE-5 *1000*, you can access them by disconnecting your USB cable from your computer and the display will change to STAND ALONE MODE.

In the Menu you will see Main Programs and when you press the down arrow ↓ you will see Biofield Program and then press the down arrow again and you will see Custom programs.

Press [Enter] and you will see the first of the Custom programs that you just downloaded. By pressing the down arrow button ↓ you can scroll through the programs until you get to the program you would like to run. Press [ENTER] when you see the name of the program you would like to run and it will then ask you if you want Manual or Automatic. Press the down arrow to switch between Manual and Automatic and then press [ENTER] when you see your choice on the display ie., when you see Automatic, press [ENTER] if you want to cycle the Tunings in the automatic mode.

Manual Mode:

If you select Manual Mode, the first Tuning will appear on the display after pressing [ENTER]. To move through each of the Tunings, press the down arrow ↓. When the Tuning is displayed on the display, you can take a measurement (Measure / Balance button in the Measure position) or you can Balance the Tuning by pressing the Measure / Balance button until you see BAL in the lower left hand corner of the display.

Auto Mode:

If you select Automatic Mode, you will first be asked some questions.

Balancing Time:

Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want each Tuning to Balance then press [Enter].

Delay: Press ↓ down arrow or ↑ up arrow to adjust the amount of time you want to wait between before the next Tuning is Balanced.

Number of Cycles: Press ↓ down arrow or ↑ up arrow to adjust the amount of times you want the program to repeat itself before it completes.

Set the SE-5 *1000* into the Balance mode (by pressing the Measure / Balance button until you see BAL in the display in the lower left hand corner) and then press [ENTER].

After the SE-5 *1000* finishes the Balancing a program, it will return to the Main Menu.

NOTES:

CHART 10

CUSTOM PROGRAM

NAME_____ HOW OFTEN: _____ Day / Week
VITALITY_____ HOW LONG: _____ Min / HOURS

DATE_____ TIME_____

	1.	2.	3.	4.	5.
1.					
2.					
3.					
4.					
5.					
6.					
7.					
8.					
9.					
10.					
11.					
12.					
13.					
14.					
15.					
16.					
17.					
18.					
19.					
20.					
21.					
22.					
23.					
24.					
25.					
26.					
27.					
28.					

CHART 11

ENERGY TRANSFER PROCEDURES

ENERGIZED WATER

Balancing energy can also be transferred into water. The source of energy for these energized-water balancing experiments is from the sample in the CELL or from the Replicator Coil of the IDF Replicator.

Method #1

A vial of water is placed on the instrument RUB PLATE for 30 seconds or longer. Switches at BALANCE, NORMAL, 100, ON, Amplitude as desired. The water picks up the balancing field energy. This energized water is reportedly used by drinking the water, or by carrying a container of the water in a pocket (within your energy fields).

The same process can be applied to any Tuning (s) or the permanent memory programs, especially the Subtle Balance and the Agricultural Program (for groceries). The output cable can be used instead of placing items on the rub plate.

Method #2

The original substance is placed in a vial on the LEFT replicating coil (Input) and the water vial (or whatever substance you want to replicate into) is placed on the RIGHT potentizing coil (Output).
Press the seven pointed Star button next to the Amplitude knob and the IDFs of the substance will be automatically replicated into your target substance.

ENERGIZING TRANSFER

SUBSTANCE	DESCRIPTION	BASE
1.		
2.		
3.		
4.		
5.		
6.		

COMPATIBILITY ANALYSIS

EXPERIMENTS TO MEASURE AND BALANCE COMPATIBILITY

PURPOSE:

To measure IDF compatibility between a subject and another subject or substance. To increase energies of weak positive compatibilities and neutralize excessive negative interferences to compatibility.

PROCEDURE: (Any programs or Tunings may be used)

1. Operator entered Tunings from research manual.
2. Operator entered Tunings of choice from listed below:
    a) Food
    b) Water
    c) Nutritional supplements or reagents
    d) Products as jewelry, crystals, gemstones, geometric patterns
    e) Persons, animals, plants

OPERATING PROCEDURES:

One operator's technique is as follows:

After turning on the SE-5 and letting neutralization occur (Display will show Clear Cell, Please Wait, then go to MAIN PROGRMS), set the switches to "Measure", "Normal" and "100", if not already at these settings. Place a Polaroid photograph from your POGO printer of the subject in the CELL. Insert the input plate. Scroll to Biofield Program and press [ENTER] and then press [ENTER] again when it says Intake Clearances. Make the usual tests for "purity of energy present" (100-0) and interfering radiations (13-78, 29-80, 50-57, 70-79). If, and only if, these five tests all read in the proper ranges, continue with the analysis.

Continue to the Tuning, overall vitality (9-49) and take Amplitude measure and record. Place a tiny specimen of the food in question onto the input plate. Again read the overall vitality and compare this reading with the previous reading taken without the food sample. If the vitality increased with the food present, the food energy is compatible and boosts the overall vitality level. If the vitality reading was lower with the food specimen the IDF level was reduced and the food apparently is not beneficial nor compatible to biofield IDF levels.

If the vitality reading remained unchanged, the food is complimentary to the vitality energy (not negating, not boosting). To continue, remove the food specimen just checked and replace it with another sample and again, measure the overall vitality Amplitude.

NOTE: Not only food specimens, but also products or substances such as vitamin and mineral supplements have been used for IDF compatibility experiments of this type.

A researcher can also use other Tunings that may provide more specific response such as IDF allergy Tunings or Tunings for different parts of the digestive tract.

CHART 12
IDF COMPATIBILITY ANALYSIS

Name _____ Date _____

_____

COMPATIBILITY ANALYSIS

SUBSTANCE	DESCRIPTION/TUNING	PRE	POST
1.			
2.			
3.			
4.			
5.			
6.			
7.			
8.			
9.			
10.			
11.			
12.			
13.			
14.			
15.			

NOTES:

APPLICATIONS - SE-5 *1000* INRINSIC DATA FIELD ANALYZER

Experimental research with the SE-5*1000* INTRINSIC DATA FIELD ANALYZER is an on-going concern and new research applications are being developed every day by hundreds of researchers using SE-5 instrumentation.

Experimental analysis and balancing research with IDF instrumentation has been reportedly used to:

- Analyze the IDF fields surrounding objects, thoughts, emotions, relationships, environments, and to send corrective signal to balance these energy fields.
- Measure subconscious reactions to questions.
- Analyze IDF correlation with various states and conditions of health and well being.
- Identify and balance interfering emotional and mental energies.
- Balance acupuncture energy meridians, points and auric energies.
- Locate and release energy blockages and stress factors which may lead to pain.
- Detect and balance excessive and deficient subtle energies in a field.
- Test for compatibility and sensitivity to foods, products, supplements, persons and environments.
- Potentization, energetic duplications and replication os substances.
- Analyze IDF field effects of various therapeutic interventions.
- Detect and neutralize subtle effects of pollutants, impurities and residues in foods, water, garden products and household environments.
- Clear and program crystals, gems and jewelry.
- Balance right and left side energy fields for efforts in superlearning and performance.
- Test and balance relationships, business and personal compatibilities.
- Program for self image, self esteem, confidence and personal growth.
- Neutralize barriers to transpersonal growth and to program affirmations and attitudes.
- Analyze and balance performance factors in achieving sports, business and personal goals.
- Locate precious metals, lost objects, artifacts, missing persons and conduct investigations.
- Analyze potential investment opportunities, sales prospects proposals and strategic planning.
- Troubleshooting mechanical problems and measuring quality control factors in products and design and engineering schematics.

OPERATOR CLEARING CODES

To prevent SE-5 *1000* operators from taking on negative vibrational frequencies from research subjects, it is recommended that the Subtle Balance Program be used. This should be done preferably after each session or at the minimum, at the end of each work day. If this does not feel adequate follow steps below.

OPERATOR CLEARING FOR NEGATIVE ENERGIES

1. Start the Operator Clearing Codes (NEG) program and Balance until stick at "000"

43-28 @ 000	Aura Disturbances
95-100 @ 000	Negative Polarity
06-12 @ 000	Negative Emotions
40-54 @ 000	Negative Etheric Influences

2. Start the Operator Clearing Codes (POS) program and Balance until stick at "100"

37-22 @ 100	Aura Coordination
42-65 @ 100	Balance Negativity
48-27 @ 100	Release Negativity
30-65 @ 100	Balance Positivity
90-62 @ 100	Balance Energy Center
12-22 @ 100	White Light

3. If this still doesn't feel adequate, Enter word Tunings, balance until stick at 100 and *1000* Amplitude. Connect to your PC and click on the W icon and type into computer "Remove dark forces, negative energies, entities, influences, broadcasts and control lines on all levels and from all sources."

Steps 1 and 2 may be used one at a time or entered all at once for 10-15 minutes at 50.
Step 3 by itself can be used for almost any problem.

If problem still remains, add 48-55 (SUBCONSCIOUS) between steps. (Follow steps to make a custom program in your PC to add 48-55 between the above Tunings.)

DOWNLOADING PROGRAMS FROM THE SE-5 1000 PC SOFTWARE INTO THE SE-5 1000.

Send Sessions to the SE-5 1000

After you have completed making a Session or several Sessions, you can download into the SE-5 1000 and store them in the instrument for portability or for balancing without the use of your PC.

1. Go to Analysis then to Session Manager.



2. Check off the Sessions you would like to send to the SE-5 1000.



3. Click on the [Send to Se-5] button.

Note: The next time you want to send Sessions to the SE-5 1000, the previous sessions will be overwritten in the SE-5. If you want to add a new Session but keep the old ones, make sure to check off ALL of the programs you want in the SE-5, not just the new one.